4) MDB MC6 US

Chipmunk
QF=5 (Neutron)
MUX Quad/Add: 0-052
ACNET Name: G:RD0052
Trip point: 5 mrem/hr (integrating mode)
Controls: Controlled Area, minimal occupancy
This detector is:

- located on the west side of the MC6 shield pile in the MDB.
- positioned at the west side of the beam line at z~5690'.
- used to limit the accident dose west of the MCenter beam line.

5) MDB MC6 Mid

Chipmunk
QF=5 (Neutron)
MUX Quad/Add: 0-053
ACNET Name: G:RD0053
Trip point: 5 mrem/hr (integrating mode)
Controls: Controlled Area, minimal occupancy
This detector is:

- located on the west side of the MC6 shield pile in the MDB.
- positioned at the west side of the beam line at z~5710'.
- used to limit the accident dose west of the MCenter beam line.

6) MDB MC6 DS

Chipmunk
QF=5 (Neutron)
MUX Quad/Add: 0-054
ACNET Name: G:RD0054
Trip point: 5 mrem/hr (integrating mode)
Controls: Controlled Area, minimal occupancy
This detector is:

- located on the west side of the MC6 shield pile in the MDB.
- positioned at the west side of the beam line at z~5730'.
- used to limit the accident dose west of the MCenter beam line.