



- 0) Bring a flashlight.
- 1) "A" and "B" enter the NM2 enclosure through the NS7 Service Building and proceed upstream to reset Interlock Box #1.
- 2) "A" holds at stairwell while "B" proceeds up the stairs sweeping the hallway to reset Interlock Box #2.
- 3) "A" and "B" sweep the tunnel going downstream to the Target Hall.
- 4) "A" holds while:
- 5) "B" checks between the Dump and the wall and inside the Dump, then moves downstream using Mirror #1 to check on top of the Dump and holds at (5A).
- 6) "A" proceeds to (6), then checks inside the downstream end of the Dump and inside the upstream end of NM2S2 and holds until making contact with "A".
- 7) "B" goes between NM2S2 and NM2S, checking between and on top of NM2S2 using the left Mirror #2 above the RAW system. "B" then goes under the beam pipe to check between NM2S2 and the wall. When "B" gets to upstream end of NM2S2, "B" will make contact with "A". After "B" has contacted "A", "B" will check around the RAW System, using the right Mirror #2 to check on top of NM2S. Again using the flashlight "B" will check inside NM2S.
- 8) "B" will then move to the sump pump pit area and use Mirror #3 above the sump pit to check the downstream area on top of NM2S. "B" will now hold looking upstream, watching the Target Hall.
- 9) While "B" is holding, "A" will continue the search.
- 10) "A" will sweep the stairwell to Interlock box #3 and reset it.
- 11) "A" will sweep the tunnel and checking all around the C-Blocks to reset Interlock box #4.
- 12) "A" will join "B", and they will sweep the stairwell to exit.
- 13) "A" and "B" will exit and reset Interlock Box #5.

Reviewed AD/RSO	Date
<i>Gary Lauton</i>	10/23/14
Approved AD/OPS Dept. Head	Date
<i>Daniel John</i>	10/23/14